

Prepayment Meters

1 Main Features

DTSY256
(QPM31-1)



DTSY256(QPM31-1)

1. Bidirectional active energy measurement
2. One card one user, ease of electricity management
3. Data security: smart card optional embedded CoS plus dynamic 3DES encryption
4. Over credit and overload power off
5. Integrated prepaid vending system and consumption inspection feature6. For details, please refer to User Manual

DTSY256(QPM32-1)

1. Energy Measurement Function: Measure forward/ reversal, active/ reactive energy
2. Instantaneous Parameters Measurement Function: measure instant active/ reactive total power, phase voltage / current/ power factor, frequency
3. Tariffs function: support TOU tariffs and step tariff
4. One card one user, ease of electricity management
5. Multi-Tariff feature(optional),configurable tariff(peak, flat, valley)and TOD
6. Data security: smart card optional embedded CoS plus dynamic 3DES encryption
7. IR and RS485,RF(optional), PLC(optional)
8. Over credit and overload power off
9. Integrated prepaid vending system and consumption inspection feature
10. For details, please refer to User Manual

DTSY256
(QPM32-1)



2 Product parameters

Specification		DTS686((QPM31-1))	DTS686(QPM32-1)
Standards		IEC 62052-11:2003 IEC 62053-21:2003 IEC 62053-23:2003	IEC 62056-21
Accuracy	Active	1.0	1.0
Voltage	Reactive	/	2.0
	Rated	3×57.7/100V~3×240/415V	3×57.7/100V~3×240/415V
Range	Range	0.8Un-1.2Un	0.8Un-1.2Un
	Limit	1.7Un-1.3 Un	1.7Un-1.3 Un
Frequency		50Hz/60Hz	50Hz/60Hz
	Current	1.5(6)A, 5(30)A, 5(60)A, 10(100)A	1.5(6)A, 5(30)A, 5(60)A, 10(100)A
Starting Current		≤0.4%lb	≤0.4%lb
	Constant	3200, 1600, 800, 400imp /KWh 3200, 1600, 800, 400imp /Kvarh	3200, 1600, 800, 400imp /KWh 3200, 1600, 800, 400imp /Kvarh
Display	Type	LCD	LCD
	Digit	6+2	6+2
Power Loss	Voltage Circuit	≤0.5W,7VA	≤0.5W,7VA
	Current Circuit	≤0.5VA	≤0.5VA
	Interface	/	Optical, RS485, RF, PLC, GPRS
Temperature Condition	Work Temperature	-25°C ~+55°C	-25°C ~+55°C
	Storage Temperature	-35°C ~+70°C	-35°C ~+70°C
Humidity		≤85°C	≤85°C
		IP54	IP54
IP degree		203×110×60mm	203×110×60mm
	Weight	Net / Gross 0.6kg/0.75kg	0.6kg/0.75kg